

Cetus

LANTERN LIGHT

The Cetus Lantern improves your indoor environment by letting in plenty of indirect daylight whilst blocking direct light. Viewed from outside or from within, its beautiful design enhances your building's overall architectural impression.

Cetus is made of the finest materials, with great attention to detail, and is built to last.

With the market's lowest U-value, Cetus can reduce your heating costs by up to 40% compared with traditional skylights. A highly insulated upstand helps to minimize heat loss. Unlike other manufacturers, Primalux will calculate the U-values for using Cetus in your specific project, and show you the potential savings on your energy costs (see U-value section overleaf).

Cetus is made bespoke to suit your needs, with glass in four sides, and an enclosed top.

This skylight is suitable for schools, offices and terrace buildings where only indirect light is needed.

Primalux products are made in Denmark by Primalux A/S, a European market leader in bespoke roof-light solutions. Our aim is to deliver the best value for skylights, when you compare building costs and consider the energy we save you over a five-year period. We offer you the best-insulated skylights on the market. Our products reduce the amount of insulation needed in your building project, saving you further money. Our skylights go further than simply conforming to national and European standards. We exceed quality and safety demands in U-values, strength against wind load, and effectiveness in fire and smoke resistance. Our vision is to lead the market in skylights through constant product development, and to continue providing our customers with well-designed, effective solutions.

- Size: Max. 1200 x 2400 mm.
Min. 500 x 500 mm.
- Upstand: Frame height:
 - Upstand (timber): From 200 mm with jumps of 50 mm
 - Frame height is measured vertically.
 Thickness of upstand:
 - Timber: 9 mm plywood/45 mm insulation/9 mm plywood.
 Light opening = roof opening
 Upstand height depends on insulation depth

DOCUMENTATION

U-Values And Your Project

All parts of buildings release heat to the surrounding environment, with some building materials insulating better than others. Fortunately, we can calculate the amount of energy passing through different materials and compare their insulative capabilities. These calculations help us to design the most energy-efficient skylights possible.

The calculations provide what is called a U-value, which measures how much energy (in Watts) is lost to the surroundings in relation to the product's surface area and the temperature difference between outside and inside.

The U-value on a skylight is affected by a variety of influences – e.g. the size of the total surface area - and the heat lost at every join on the construction. Each time a new material is used, a calculation must be made for that specific material.

Together, these calculations enable the manufacturer to state the total and correct U-value for the specific construction.


Primalux are happy to supply fully documented calculations for your specific project, thereby showing you the potential energy savings.

CE standards state that manufacturers must be able to specify the U-value on any given finished product in your project, in order for you to calculate your exact heat loss and the overall heat loss for the building.


For more details on Primalux and on specific Primalux products, please contact:

Panel Agency
Phone: +44 (0)1474-872578
Fax: +44 (0)1474-872426.
Email: sales@panelagency.com

Panel Agency, Maple House, 5 Over Minnis, New Ash Green, Longfield Kent DA3 8JA United Kingdom



Example of where heat loss must be calculated on an acrylic dome skylight



Example of where heat loss must be calculated on a glass skylight



Thermal cross section: Less heat loss indicated by the red colour